



### 3. IP RATING

#### What is an IP rating?

IP (or "Ingress Protection") ratings are used to define levels of sealing effectiveness of electrical enclosures against intrusion from foreign bodies (tools, dirt etc) and moisture. Below are the most popular ratings.

#### INDOOR

- IP20 - suitable for any indoor areas that may be exposed to steam, condensation, or water drips (such as kitchens)
- IP44 - great for most covered outdoor applications. Products with this rating should not be exposed to excessive heavy rains.


#### OUTDOOR / DAMP ENVIRONMENTS

- IP65 Enclosure - IP rated as "dust tight" and protected against water projected from a nozzle.
- IP66 Enclosure - IP rated as "dust tight" and protected against heavy seas or powerful jets of water.
- IP 67 Enclosures - IP rated as "dust tight" and protected against immersion. for 30 minutes at depths 150mm - 1000mm
- IP 68 Enclosures - IP rated as "dust tight" and protected against complete, continuous submersion in water.

**IP20 & IP68 ARE INVENTORY PRODUCTS. ALL OTHER IP RATINGS ARE SPECIAL ORDER**

### 3. TRIM LENGTH AND LENGTH OF CUT

LED strips can be cut to custom lengths indicated on each strip. With variable distances between LED chips on flexible strips, one must be discerning on the application and the cut length to avoid "dead spots" If you are lighting under cabinets you want to make sure that there is an even amount of LED's under the entire cabinet length. 30 LEDs per meter strip led chips are farther apart and may be hard to evenly light the entire area, 60 LEDs per meter are closer together.



### 4. VOLTAGE

#### Which voltage do I choose 12V or 24V?

Both 12V and 24V fall within low voltage lighting, with 12V being the more common specification. But which is best for you depends on a variety of factors.

1) Do you need to cut the LED strips to a particular length?

12V LED strips come in 3 LEDs per cut length, and 24V LED strips come in 6 LEDs per cut length. That means that 12V LED strips are cuttable every 3 LEDs, while 24V LED strips are cuttable every 6 LEDs.

Depending on the LED density, cutting every 6 LEDs on a 24V strip could mean that your length options come in increments of 3" instead of 1.5" at 12V.

3) Do you not have a preference?

All else bring equal, a 24V system will perform better.

Generally, the same product being offered in 12V and 24V will have the same number of LEDs with the same power and light output, but simply different voltage and amperage combination.

For example, a 24W per meter LED strip at 12V would draw 2.0A per meter, while the 24V variant would draw 1.0A per meter. Both will draw 24W and provide the same amount of light output, but because the 24V variant draws less amperage, it will generally perform better internally in the LED strip as well as at the power supply.

This is because resistance is determined by amperage only, and is independent of voltage. Therefore, all else equal, the lower amperage option (24V) will perform better electrically.

SPECIFICATION  
**IL-TG-RGB-5050-30**  
 THINGLOW SERIES

PROJECT	DATE
TYPE	QTY



**FLEXIBLE LED STRIPS FOR COVE AND STEP LIGHTING**

**INDOOR RGB**

**IL-TG-RGB-5050-30-IP20**

- IP20 (Non-Waterproof) SMD 5050 Flexible LED Strip
- LED Qty: 30LED s/m
- Dimensions: 500mm x 10mm x 0.22mm
- Voltage: DC12/24V
- Power Consumption: (12V/24) 7.2 W/m
- 3/6 LED cuttable
- Dimmable with suitable driver or controller


**OUTDOOR RGB**

**IL-TG-RGB-5050-30-IP68**

- IP68 (Waterproof) SMD 5050 Flexible LED Strips, Silicone Tube + Silicone Glue
- LED Qty: 30LED s/m
- PCB Dimension: 500mm x 10mm x 0.22mm
- Voltage: DC12/24V
- Power Consumption: (12V/24) 7.2 W/m
- 3/6 LED cuttable
- Dimmable with suitable driver or controller




**RGB - 5050 - 12V - 30LED/m - 7.2 W/m**



V. 320 | Copyright © 2020, Impact Lighting Inc. All Rights Reserved

**RGB - 5050 - 24V - 30LED/m - 14.4 W/m**



**ORDERING**

MODEL	IP Rating	Voltage	No. Reels
<b>IL-TG-RGB-5050-30</b>	— <input type="text"/>	— <input type="text"/>	— <input type="text"/>
ThinGlow™ RGB-5050 30 LED/m Flexible LED Strip	20 - IP20 68 - IP68	12 - 12V 24 - 24V	Write number of reels needed above

SPECIFICATION  
**IL-TG-RGB-5050-60**  
 THINGLOW SERIES

PROJECT	DATE
TYPE	QTY



**FLEXIBLE LED STRIPS FOR COVE AND STEP LIGHTING**

**INDOOR RGB**

**IL-TG-RGB-5050-60-IP20**

- IP20 (Non-Waterproof) SMD 5050 Flexible LED Strip
- LED Qty: 60LED s/m
- Dimensions: 500mm x 10mm x 0.22mm
- Voltage: DC12/24V
- Power Consumption: (12V/24) 14.4 W/m
- 3/6 LED cuttable
- Dimmable with suitable driver or controller


**OUTDOOR RGB**

**IL-TG-RGB-5050-60-IP68**


- IP68 (Waterproof) SMD 5050 Flexible LED Strips, Silicone Tube + Silicone Glue
- LED Qty: 60LED s/m
- PCB Dimension: 500mm x 10mm x 0.22mm
- Voltage: DC12/24V
- Power Consumption: (12V/24) 14.4 W/m
- 3/6 LED cuttable
- Dimmable with suitable driver or controller



**RGB - 5050 - 12V - 60LED/m - 14.4 W/m**



**RGB - 5050 - 24V - 60LED/m - 14.4W/m**



**ORDERING**

MODEL	IP Rating	Voltage	No. Reels
<b>IL-TG-RGB-5050-60</b>			
ThinGlow™ RGB-5050 60 LED/m Flexible LED Strip	20 - IP20 68 - IP68	12 - 12V 24 - 24V	Write number of reels needed above

V.320 | Copyright © 2020, Impact Lighting Inc. All Rights Reserved

SPECIFICATION  
**IL-TG-RGBX-5050-30**  
 THINGLOW SERIES

PROJECT	DATE
TYPE	QTY



**INDOOR RGBX**

**IL-TG-RGBX-5050-30-IP20**

- IP20 (Non-Waterproof) SMD 5050 Flexible LED Strip
- LED Qty: 30LED s/m
- Dimensions: 500mm x 12mm x 0.22mm
- Voltage: DC12/24V
- Power Consumption: (12V/24) 7.2 W/m
- 3/6 LED cuttable
- Dimmable with suitable driver or controller


**OUTDOOR RGBX**

**IL-TG-RGBX-5050-30-IP68**

- IP68 (Waterproof) SMD 5050 Flexible LED Strips, Silicone Tube + Silicone Glue
- LED Qty: 30LED s/m
- PCB Dimension: 500mm x 12mm x 0.22mm
- Voltage: DC12/24V
- Power Consumption: (12V/24) 7.2 W/m
- 3/6 LED cuttable
- Dimmable with suitable driver or controller




**RGBX-5050 - 12V - 30LED/m - 7.2W/m**



V. 320 | Copyright © 2020, Impact Lighting Inc. All Rights Reserved

**RGBx - 5050 - 24V - 60LED/m - 7.2W/m**



**ORDERING**

MODEL	IP Rating	Voltage	No. Reels
<b>IL-TG-RGBX-5050-30</b>	-	-	-
ThinGlow™ RGBX-5050 30 LED/m Flexible LED Strip	20 - IP20 68 - IP68	12 - 12V 24 - 24V	Write number of reels needed above

SPECIFICATION  
**IL-TG-RGBX-5050-60**  
 THINGLOW SERIES

PROJECT	DATE
TYPE	QTY



**FLEXIBLE LED STRIPS FOR COVE AND STEP LIGHTING**

**INDOOR RGBX**

**IL-TG-RGBX-5050-60-IP20**

- IP20 (Non-Waterproof) SMD 5050 Flexible LED Strip
- LED Qty: 60LED s/m
- Dimensions: 500mm x 12mm x 0.22mm
- Voltage: DC12/24V
- Power Consumption: (12V/24) 14.4 W/m
- 3/6 LED cuttable
- Dimmable with suitable driver or controller


**OUTDOOR RGBX**

**IL-TG-RGBX-5050-60 IP68**


- IP68 (Waterproof) SMD 5050 Flexible LED Strips, Silicone Tube + Silicone Glue
- LED Qty: 60LED s/m
- PCB Dimension: 500mm x 13mm x 0.22mm
- Voltage: DC12/24V
- Power Consumption: (12V/24) 14.4 W/m
- 3/6 LED cuttable
- Dimmable with suitable driver or controller



**RGBX-5050 - 12V - 60LED/m - 19.2W/m**



**RGBX-5050 - 24V - 60LED/m - 19.2W/m**



**ORDERING**

MODEL	IP Rating	Voltage	No. Reels
<b>IL-TG-RGBX-5050-60</b>			
ThinGlow™ RGBX-5050 60 LED/m Flexible LED Strip	20 - IP20 68 - IP68	12 - 12V 24 - 24V	Write number of reels needed above

SPECIFICATION  
**IL-TG-WW-2538-60**  
 THINGLOW SERIES

PROJECT	DATE
TYPE	QTY



**FLEXIBLE LED STRIPS FOR COVE AND STEP LIGHTING**

**INDOOR WW**

**IL-TG-WW-2538-60-IP20**

- IP20 (Non-Waterproof) SMD 5050 Flexible LED Strip
- LED Qty: 60LED s/m
- Dimensions: 500mm x 10mm x 0.22mm
- Voltage: DC 12/24V
- Power Consumption: (12V/24) 4.8 W/m
- 3/6 LED cuttable
- Dimmable with suitable driver or controller


**OUTDOOR WW**

**IL-TG-WW-2538-60-IP68**


- IP68 (Waterproof) SMD 5050 Flexible LED Strips, Silicone Tube + Silicone Glue
- LED Qty: 60LED s/m
- PCB Dimension: 500mm x 10mm x 0.22mm
- Voltage: DC 12/24V
- Power Consumption: (12V/24) 4.8 W/m
- 3/6 LED cuttable
- Dimmable with suitable driver or controller



**WW-2538 12V - 60LED/m - 19.2W/m**



**WW-2538 24V - 60LED/m - 19.2W/m**



**ORDERING**

MODEL	IP Rating	Voltage	No. Reels
<b>IL-TG-WW-2538-60</b>	-	-	-
ThinGlow™ WW-2538 60 LED/m Flexible LED Strip	20 - IP20 68 - IP68	12 - 12V 24 - 24V	Write number of reels needed above

SPECIFICATION  
**IL-TG-WW-2538-240**  
 THINGLOW SERIES

PROJECT	DATE
TYPE	QTY



**FLEXIBLE LED STRIPS FOR COVE AND STEP LIGHTING**



**INDOOR WW**

**IL-TG-WW-2538-240-IP20**


- IP20 (Non-Waterproof) SMD 5050 Flexible LED Strip
- LED Qty: 240LED s/m
- Dimensions: 500mm x 6mm x 0.22mm
- Voltage: DC 12/24V
- Power Consumption: (12V/24) 19.2 W/m
- 3/6 LED cuttable
- Dimmable with suitable driver or controller

**OUTDOOR WW**


**IL-TG-WW-2538-240-IP68**

- IP68 (Waterproof) SMD 5050 Flexible LED Strips, Silicone Tube + Silicone Glue
- LED Qty: 240LED s/m
- PCB Dimension: 500mm x 6mm x 0.22mm
- Voltage: DC 12/24V
- Power Consumption: (12V/24) 19.2 W/m
- 3/6 LED cuttable
- Dimmable with suitable driver or controller

**WW-2538 12V - 240 LED/m - 19.2W/m**



**WW-2538 24V - 240LED/m - 19.2W/m**



**ORDERING**

MODEL	IP Rating	Voltage	No. Reels
<b>IL-TG-WW-2538-240</b>			
ThinGlow™ Warm White 240 LED/m Flexible LED Strip	20 - IP20 68 - IP68	12 - 12V 24 - 24V	Write number of reels needed above

V.320 | Copyright © 2020, Impact Lighting Inc. All Rights Reserved



SPECIFICATION  
**IL-TG-CW-2538-60**  
 THINGLOW SERIES

PROJECT	DATE
TYPE	QTY



**FLEXIBLE LED STRIPS FOR COVE AND STEP LIGHTING**

**INDOOR CW**

**IL-TG-CW-2538-60-IP20**

- IP20 (Non-Waterproof) SMD 5050 Flexible LED Strip
- LED Qty: 60LED s/m
- Dimensions: 500mm x 10mm x 0.22mm
- Voltage: DC 12/24V
- Power Consumption: (12V/24) 4.8 W/m
- 3/6 LED cuttable
- Dimmable with suitable driver or controller


**OUTDOOR CW**

**IL-TG-CW-2538-60-IP68**

- IP68 (Waterproof) SMD 5050 Flexible LED Strips, Silicone Tube + Silicone Glue
- LED Qty: 60LED s/m
- PCB Dimension: 500mm x 10mm x 0.22mm
- Voltage: DC 12/24V
- Power Consumption: (12V/24) 4.8 W/m
- 3/6 LED cuttable
- Dimmable with suitable driver or controller




**CW-2538 12V - 60LED/m - 19.2W/m**



V.320 | Copyright © 2020, Impact Lighting Inc. All Rights Reserved

**CW-2538 24V - 60LED/m - 19.2W/m**



**ORDERING**

MODEL	IP Rating	Voltage	No. Reels
<b>IL-TG-CW-2538-60</b>			
ThinGlow™ Cool White 60 LED/m Flexible LED Strip	20 - IP20 68 - IP68	12 - 12V 24 - 24V	Write number of reels needed above

SPECIFICATION  
**IL-TG-CW-2538-60**  
 THINGLOW SERIES

PROJECT	DATE
TYPE	QTY



**FLEXIBLE LED STRIPS FOR COVE AND STEP LIGHTING**

**INDOOR CW**

**IL-TG-CW-2538-60-IP20**

- IP20 (Non-Waterproof) SMD 5050 Flexible LED Strip
- LED Qty: 60LED s/m
- Dimensions: 500mm x 10mm x 0.22mm
- Voltage: DC 12/24V
- Power Consumption: (12V/24) 4.8 W/m
- 3/6 LED cuttable
- Dimmable with suitable driver or controller


**OUTDOOR CW**

**IL-TG-CW-2538-60-IP68**

- IP68 (Waterproof) SMD 5050 Flexible LED Strips, Silicone Tube + Silicone Glue
- LED Qty: 60LED s/m
- PCB Dimension: 500mm x 10mm x 0.22mm
- Voltage: DC 12/24V
- Power Consumption: (12V/24) 4.8 W/m
- 3/6 LED cuttable
- Dimmable with suitable driver or controller




**CW-2538 12V - 60LED/m - 19.2W/m**



V.320 | Copyright © 2020, Impact Lighting Inc. All Rights Reserved

**CW-2538 24V - 60LED/m - 19.2W/m**



**ORDERING**

MODEL	IP Rating	Voltage	No. Reels
<b>IL-TG-CW-2538-60</b>			
ThinGlow™ Cool White 60 LED/m Flexible LED Strip	20 - IP20 68 - IP68	12 - 12V 24 - 24V	Write number of reels needed above